

Free standing Battery Energy Storage System

Introduce the LIFEP04 Power Wall battery for residential energy storage a fashionable home energy storage solution. The battery is equipped with Superior quality smart BMS to monitor the battery and multiple protection. The UNIV-Power Wall series lithium battery allows parallel connection to enhance capacity, and can easily monitor its working conditions by uplink and optional bluetooth. The extraordinary compatibility of it with the extensive inverter brand ensures seamless integration into your energy system. Select the UNIV-Power Wall series battery to ensure a reliable and continuous power supply ultimate energy demand selection.

Features And Advantages



Simple and Elegant
Appearance



Easy Moving with
Wheels design



Versatile Modules



10 Years Warranty



Superior BMS with
Brand Battery Cell



> 8000 Cycle Times



Residential Energy
Storage



Large Scalability

Lithium Battery



Specification

MODEL		UNIV-10kWhFS
BATTERY PARAMETERS		
Total Energy (kWh)		10.24
Useable Energy (kWh)		9.63
Nominal Voltage (Vd.c)		51.2
Voltage Range (Vd.c)		44.8 ~ 57.6
Rated Capacity (Ah)		200
Recommend Current (A)	Charge	160
	Discharge	160
Max. Current (A)	Charge	150
	Discharge	150
Recommend Using DOD		90%
Scalability		Max 16 in Parallel
Dimension (W *H* D)(mm)		760*560*145
Weight (KG)		86
BMS Features		Over-voltage & Over-current Protection/Short-circuit Protection Low-voltage Protection/Over Temperature Protection/Cell Balance
Communication		CAN/RS485/RS232
OPERATING CONDITION		
Operation Temperature	Charge	0°C ~ 55°C (32°F ~ 131°F)
	Discharge	-20°C~55°C(-4°F~131°F)
Storage Temperature		-20°C~55°C(-4°F~131°F)
IP Rating		IP54
Installation Type		Free-Standing
Cooling Type		Natural
Operating Environment		Indoor (5% ~ 95%(RH) No Condensing)
Altitude		≤4000 m
CERTIFICATION AND		
Warranty		10 Years
Operation Life		15+ Years (25°C/77 °F)
Cycle Life		≥8000@25°C
Certification		CE/Cell UL 1973
Transportation Certification		UN38.3/MSDS

The recommended and max. continuous operation current is for a battery cell temperature within 10~40°C to consider, out of such temp. range will cause a derating on operation current.